

### Extra Dark Charcoal Colour

Total Solar Energy Rejected (TSER)	64%
Visible Light Transmitted	10%
Visible Light Reflected	8%
Ultra Violet Rejected	>99%
Glare Reduction	86%
Metallised	✓
Scratch Resistant Coating	✓
Adhesive Type	HPR

<sup>\*</sup>Data derived from application to Pilkington automotive green glass 4mm with a 78% VLT





### Dark Charcoal Colour

Total Solar Energy Rejected (TSER)	62%
Visible Light Transmitted	19%
Visible Light Reflected	10%
Ultra Violet Rejected	>99%
Glare Reduction	78%
Metallised	✓
Scratch Resistant Coating	✓
Adhesive Type	HPR

<sup>\*</sup>Data derived from application to Pilkington automotive green glass 4mm with a 78% VLT.





### **Charcoal Colour**

Total Solar Energy Rejected (TSER)	58%
Visible Light Transmitted	35%
Visible Light Reflected	10%
Ultra Violet Rejected	>99%
Glare Reduction	60%
Metallised	✓
Scratch Resistant Coating	✓
Adhesive Type	HPR

<sup>\*</sup>Data derived from application to Pilkington automotive green glass 4mm with a 78% VLT.





# **Light Charcoal Colour**

Total Solar Energy Rejected (TSER)	41%
Visible Light Transmitted	45%
Visible Light Reflected	8%
Ultra Violet Rejected	99%+
Glare Reduction	49%
Metallised	✓
Scratch Resistant Coating	✓
Adhesive Type	HPR

<sup>\*</sup>Data derived from application to Pilkington automotive green glass 4mm with a 78% VLT.





# JetBlack 22 Non-Metallised

### Dark Charcoal Colour

Total Solar Energy Rejected (TSER)	51%
Visible Light Transmitted	20%
Visible Light Reflected	6%
Ultra Violet Rejected	>99%
Glare Reduction	75%
Non-Metallised	✓
Scratch Resistant Coating	✓
Adhesive Type	HPR

<sup>\*</sup>Data derived from application to Pilkington automotive green glass 4mm with a 78% VLT.





## JetBlack 35 Non-Metallised

### **Charcoal Colour**

Total Solar Energy Rejected (TSER)	47%
Visible Light Transmitted	35%
Visible Light Reflected	5%
Ultra Violet Rejected	>99%
Glare Reduction	58%
Non-Metallised	✓
Scratch Resistant Coating	✓
Adhesive Type	HPR

<sup>\*</sup>Data derived from application to Pilkington automotive green glass 4mm with a 78% VLT.

