

# N1035 Bronze

## Solar Control Series

### Performance Data:

Total Solar Energy Rejected (Heat)	64%
Visible Light Transmitted	37%
Visible Light Reflected (External)	26%
Ultra Violet Rejected	99%
Shading Coefficient	0.41
SHGC	0.36
U-Value – (Winter)	5.23
Glare Reduction	59%
Solar Energy Reflected	37%
Solar Energy Absorbed	37%
Estimated Fade Reduction*	70%

### Benefits:

- W.E.R.S. Rating 4 Stars (cooling).
- Ideal for commercial and residential application.
- Advanced sputtering technology.
- Only stabilised metals used in production.
- Original colour guaranteed to last.
- Rejects 62% of heat.
- Reduces energy costs all year round.
- Provides daytime privacy.
- Good glare reduction.
- Strengthens glass for added safety.
- Over 98% of harmful UV rejected.
- Very good fade reduction.
- World's toughest scratch resistant surface.
- Clear distortion free adhesive.
- Lifetime warranty residential - not transferable.
- 12 year warranty commercial - not transferable.

#### APPLIED TO 6MM CLEAR GLASS

\*This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.

Note: It is the sellers/installers responsibility to determine application & 'duty of care' requirements as required by building standards.



mepfilms