

N1035 Neutral

Solar Control Series

Performance Data:

Total Solar Energy Rejected (Heat)	51%
Visible Light Transmitted	37%
Visible Light Reflected (External)	19%
Ultra Violet Rejected	99%
Shading Coefficient	0.56
SHGC	0.49
U-Value – (Winter)	5.96
Glare Reduction	59%
Solar Energy Reflected	17%
Solar Energy Absorbed	49%
Estimated Fade Reduction*	67%

Benefits:

- W.E.R.S. Rating 2.5 Stars (cooling)/0.5 star (heating).
- Ideal for commercial buildings on clear glass.
- Advanced sputtering technology.
- Popular film for homes.
- Only stabilised metals used in production.
- Original colour guaranteed to last.
- Rejects 53% of heat.
- Provides daytime privacy.
- Good glare reduction.
- Strengthens glass for added safety.
- Over 98% of harmful UV rejected.
- Very good fade reduction.
- World's toughest scratch resistant surface.
- Clear distortion free adhesive.
- Lifetime warranty residential - not transferable.
- 12 year warranty commercial - not transferable.

APPLIED TO 6MM CLEAR GLASS

*This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.



mepfilms