

N1050 (8) CLEAR (200 MICRONS)

Magnum Safety Series

Performance Data:

Total Solar Energy Rejected (Heat)	39%
Visible Light Transmitted	49%
Visible Light Reflected (External)	11%
Ultra Violet Rejected	>99%
Shading Coefficient	0.70
SHGC	0.61
U-Value – (Winter)	6.08
Glare Reduction	46%
Solar Energy Reflected	10%
Solar Energy Absorbed	42%
Estimated Fade Reduction*	63%

Benefits:

- W.E.R.S. Rating 2 Stars (cooling/ 0.5 star (heating).
- Maximum protection security film.
- Manufactured to comply with Safety Glazing Standard AS/NZS2208 when applied to 3mm glass and above.
- Multi-layer film construction.
- 44% heat reduction.
- Reduces 45% of glare.
- Almost six times thicker than normal film, substantially increasing strength and safety features (200 micron).
- World's toughest scratch resistant surface.
- 4.5kg (10lb) pressure sensitive mounting adhesive.
- Puncture strength 164 pounds force.
- Lifetime warranty residential - not transferable.
- 12 year warranty commercial - not transferable.
- Physical properties available upon request.

APPLIED TO 6MM CLEAR GLASS

*This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.

Note: It is the sellers/installers responsibility to determine application & 'duty of care' requirements as required by building standards.



mepfilms