

N1050 Neutral

Solar Control Series

Performance Data:

Total Solar Energy Rejected (Heat)	41%
Visible Light Transmitted	50%
Visible Light Reflected (External)	14%
Ultra Violet Rejected	99%
Shading Coefficient	0.68
SHGC	0.59
U-Value – (Winter)	6.08
Glare Reduction	44%
Solar Energy Reflected	12%
Solar Energy Absorbed	42%
Estimated Fade Reduction*	63%

Benefits:

- W.E.R.S. Rating 2 Stars (cooling)/0.5 (heating).
- Ideal for commercial and residential application.
- Advanced sputtering technology.
- Only stabilised metals used in production.
- Original colour guaranteed to last.
- Rejects 44% of heat.
- Glare reduction.
- Strengthens glass for added safety.
- Over 98% of harmful UV rejected.
- Good fade reduction.
- World's toughest scratch resistant surface.
- Clear distortion free adhesive.
- Lifetime warranty residential - not transferable.
- 12 year warranty commercial - not transferable.

APPLIED TO 6MM CLEAR GLASS

*This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.

Note: It is the sellers/installers responsibility to determine application & 'duty of care' requirements as required by building standards.



mepfilms